



MICRON FILTER MEMBRANEH						
Model	Mesh count		Thread dia (µm)	Mesh opening (µm)	Thickness (µm)	Weight (g/m2)
	CM	Inch	Tillead dia (µIII)	westropering (µm)	THICKHESS (µIII)	Weight (g/m2)
NL120/48	120	300	35	48	60	37
NL120/40	120	300	43	40	73	55
NL130/42	130	330	35	42	60	40
NL130/34	130	330	43	34	73	61
NL140/36	140	350	35	36	60	43
NL157/25	157	400	43	25	73	74
NL180/20	180	450	39	20	66	68
NL200/15	200	500	39	15	66	76
NL220/10	220	550	39	10	66	84
NL240/5	240	600	39	5	66	91

## Information:

Product Name: Micron Filter Membrane

Materials: PA6, PA66, PET

Specification: JPP120-JPP240 (50UM-5UM)

Weave Type:plain, twill, dutch weave

Width: 100cm, 127cm, 183cm, or customized

Product Form: Rolls

Roll Length: 30-100m/Roll, Fixed Length, or customized

Color: Natural or white, or customized

## Advantage:

The mesh openings are uniform, stable, elastic, wear-resistant, smooth, alkali-resistant, easy to clean and light in texture.

## Application:

Mainly used in liquid filtration, powder filtration, petroleum, mining, pharmaceutical, chemical plant, paint, ink, oil product filtration, alcohol filtration, paint filtration, dye filtration, resin, monosodium glutamate, aquaculture, impurity filtration, food and other industrial screening and filtering.

MACROKUN MESH TEL: +86-13803219803 E-mal: sales@macrokun.com Web: www.macrokunmesh.com