



MICRON FILTER MESH						
Model	Mesh count		Thread dia (µm)	Mesh opening (µm)	Thickness (µm)	Weight (g/m2)
	CM	Inch		meen opening (pm)	(µm)	
NL120/48	120	300	35	48	60	37
NL120/40	120	300	43	40	73	55
NL130/42	130	330	35	42	60	40
NL130/34	130	330	43	34	73	61
NL140/36	140	350	35	36	60	43
NL157/25	157	400	43	25	73	74
NL180/20	180	450	39	20	66	68
NL200/15	200	500	39	15	66	76
NL220/10	220	550	39	10	66	84
NL240/5	240	600	39	5	66	91

Information:

Product Name: Micron Filter Membrane Materials: PA6, PA66, PET Specification: JPP120-JPP240 (50UM-5UM) Weave Type: Plain, Twill, Dutch weave Width: 100cm, 127cm, 183cm, or customized Product Form: Rolls Roll Length: 30-100m/Roll, Fixed Length, or customized Color: Natural or white, or customized

Advantage:

The mesh openings are uniform, stable, elastic, wear-resistant, smooth, alkali-resistant, easy to clean and light in texture.

Application:

Mainly used in liquid filtration, powder filtration, petroleum, mining, pharmaceutical, chemical plant, paint, ink, oil product filtration, alcohol filtration, paint filtration, dye filtration, resin, monosodium glutamate, aquaculture, impurity filtration, food and other industrial screening and filtering.