

Polyester Filter Mesh (涤纶过滤网)

Model	Specific ation (/cm)	Mesh count (mesh/inch)	Thread Diameter (um)	Mesh opening (um)	Thicknes s (um)	Weight (g/m2)
SS-PET4/1931	4	10	550	1931	1089	303
SS-PET6/1254	6	15	400	1254	792	240
SS-PET7/1068	7	18	300	1117	594	162
SS-PET8/941	8	20	300	941	594	180
SS-PET8/891	8	20	350	891	693	245
SS-PET10/743	10	25	250	743	495	156
SS-PET12/677	12	30	150	677	297	68
SS-PET12/578	12	30	250	578	495	188
SS-PET14/489	14	36	200	489	340	144
SS-PET16/404	16	40	200	404	340	160
SS-PET20/399	20	50	80	399	136	32
SS-PET20/380	20	50	100	380	170	50
SS-PET20/361	20	50	120	361	204	72
SS-PET20/333	20	50	150	333	255	113
SS-PET22/356	22	55	80	356	136	35
SS-PET24/320	24	60	80	320	136	38
SS-PET24/301	24	60	100	301	170	60
SS-PET24/282	24	60	120	282	204	86
SS-PET24/253	24	60	150	253	255	135
SS-PET29/214	29	74	120	214	204	107
SS-PET32/236	32	80	64	236	109	33
SS-PET32/221	32	80	80	221	136	51
SS-PET32/202	32	80	100	202	170	80
SS-PET34/184	34	86	100	184	170	86
SS-PET36/169	36	90	100	169	170	90
SS-PET39/191	39	100	55	191	94	30
SS-PET39/168	39	100	80	168	136	64
SS-PET39/149	39	100	100	149	170	100
SS-PET43/145	43	110	80	145	136	70
SS-PET47/150	47	120	55	150	94	36
SS-PET47/135	47	120	71	135	121	60
SS-PET53/134	53	135	48	134	82	31
SS-PET53/127	53	135	55	127	94	41
SS-PET53/118	53	135	64	118	109	55
SS-PET53/112	53	135	71	112	121	68

SS-PET59/115	59	150	48	115	82	35
SS-PET59/109	59	150	55	109	94	45
SS-PET59/100	59	150	64	100	109	61
SS-PET64/103	64	160	48	103	82	37
SS-PET64/96	64	160	55	96	94	48
SS-PET64/88	64	160	64	88	109	66
SS-PET72/86	72	180	48	86	82	41
SS-PET72/80	72	180	55	80	94	54
SS-PET77/71	77	195	55	71	94	59
SS-PET80/73	80	200	48	73	82	46
SS-PET90/68	90	230	40	68	68	37
SS-PET90/60	90	230	48	60	82	53
SS-PET100/51	100	250	40	51	68	40
SS-PET110/43	110	280	40	43	68	45
SS-PET120/42	120	300	34	42	58	35
SS-PET120/37	120	300	40	37	68	48
SS-PET130/36	130	330	34	36	58	38
SS-PET140/32	140	350	34	32	58	40
SS-PET150/31	150	380	30	31	51	34
SS-PET165/25	165	420	31	25	53	40

Product Name:Polyester filter mesh

Material: Polyester is also called polyester (PET) material.

Specification: DPP7-DPP165 (18-420 mesh)

Weave Type:plain, twill, dutch weave

Width: 115 cm, 127 cm, 145 cm, 165 cm, maximum 365 cm, or customized

Product Form: rolls

Roll Length: 30-100m/Roll, Fixed Length, or customized

Color: white, yellow, black, or customized

Advantages:

Good acid resistance, temperature resistance, wear resistance, easy cleaning, high tensile strength, good air permeability

Usage:

Mainly used for liquid filtration, powder filtration, petroleum, mining, pharmaceutical, chemical plant, paint, ink, oil product filtration, alcohol filtration, paint filtration, dye filtration, resin, monosodium glutamate, aquaculture, impurity filtration, food and other industrial screening and filtering.