



POLYESTER FILTER MESH

Model	Specification (cm)	Mesh count (mesh/inch)	Thread diameter (μm)	Mesh opening (μm)	Thickness (μm)	Weight (g/m ²)
PET4/1931	4	10	550	1931	1089	303
PET6/1254	6	15	400	1254	792	240
PET7/1068	7	18	300	1117	594	162
PET8/941	8	20	300	941	594	180
PET8/891	8	20	350	891	693	245
PET10/743	10	25	250	743	495	156
PET12/677	12	30	150	677	297	68
PET12/578	12	30	250	578	495	188
PET14/489	14	36	200	489	340	144
PET16/404	16	40	200	404	340	160
PET20/399	20	50	80	399	136	32
PET20/380	20	50	100	380	170	50
PET20/361	20	50	120	361	204	72
PET20/333	20	50	150	333	255	113
PET22/356	22	55	80	356	136	35
PET24/320	24	60	80	320	136	38
PET24/301	24	60	100	301	170	60
PET24/282	24	60	120	282	204	86
PET24/253	24	60	150	253	255	135
PET29/214	29	74	120	214	204	107
PET32/236	32	80	64	236	109	33
PET32/221	32	80	80	221	136	51
PET32/202	32	80	100	202	170	80
PET34/184	34	86	100	184	170	86
PET36/169	36	90	100	169	170	90
PET39/191	39	100	55	191	94	30
PET39/168	39	100	80	168	136	64
PET39/149	39	100	100	149	170	100
PET43/145	43	110	80	145	136	70
PET47/150	47	120	55	150	94	36
PET47/135	47	120	71	135	121	60
PET53/134	53	135	48	134	82	31
PET53/127	53	135	55	127	94	41
PET53/118	53	135	64	118	109	55

PET53/112	53	135	71	112	121	68
PET59/115	59	150	48	115	82	35
PET59/109	59	150	55	109	94	45
PET59/100	59	150	64	100	109	61
PET64/103	64	160	48	103	82	37
PET64/96	64	160	55	96	94	48
PET64/88	64	160	64	88	109	66
PET72/86	72	180	48	86	82	41
PET72/80	72	180	55	80	94	54
PET77/71	77	195	55	71	94	59
PET80/73	80	200	48	73	82	46
PET90/68	90	230	40	68	68	37
PET90/60	90	230	48	60	82	53
PET100/51	100	250	40	51	68	40
PET110/43	110	280	40	43	68	45
PET120/42	120	300	34	42	58	35
PET120/37	120	300	40	37	68	48
PET130/36	130	330	34	36	58	38
PET140/32	140	350	34	32	58	40
PET150/31	150	380	30	31	51	34
PET165/25	165	420	31	25	53	40

Information:

Product name: Polyester filter mesh

Materials: Polyester is also called polyester (PET) material.

Specification: DPP7-DPP165 (18-420 mesh)

Weave Type: Plain weave, Twill weave, Dutch weave

Width: 115 cm, 127 cm, 145 cm, 165 cm, maximum 365 cm, or customized

Product Form: Rolls

Roll Length: 30-100m/Roll, Fixed Length, or customized

Color: White, or customized

Advantage:

Good acid resistance, temperature resistance, wear resistance, easy cleaning, high tensile strength, good air permeability.

Application:

Mainly used for liquid filtration, powder filtration, petroleum, mining, pharmaceutical, chemical plant, paint, ink, oil product filtration, alcohol filtration, paint filtration, dye filtration, resin, monosodium glutamate, aquaculture, impurity filtration, food and other industrial screening and filtering.